



## SM07C Rear Vision System

7-inch HD Digital LCD screen with ultra-clear image in a durable housing  
 3 AV inputs with built in controller for trigger screen activation  
 Clear sound speaker, easy to use advance operation menu  
 Back-lighted buttons and monitor have auto dimming feature  
 Built for demands of commercial use



## MONITOR SPECIFICATIONS MK07C

Screen size: 7-inch digital screen (16:9)  
 High Resolution: 2400 x 480 Pixel (RGB)  
 System: PAL/NTSC auto per input  
 Contrast: 500:1 Brightness: 400 cd/m2  
 Power supply: DC 12V~32V with reverse polarity protection  
 Operation temperatures: -20°~70°C  
 Storage temperature: -30°~80°C  
 3 labeled AV inputs with labeled trigger wires, auto blue screen if no signal  
 Features: HD sunshade, headphone jack, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality USA Techwell® processor  
 Easy to use OSD menu function via buttons & remote: reversing image delay time 0~10s, (for side cameras) Mirror/Normal image, plus horizontal flip per signal channel (text stays in normal view for readability), multi-language, guidelines.

## CAMERA SPECIFICATIONS C001C

1 / 3" COLOR CCD SENSOR  
 With Audio and IR  
 Viewing angle: 130°  
 Waterproof: IP69K  
 TV System: NTSC  
 Aluminum housing waterproof camera with Allen screws for insured positioning  
 Image Type: 1/3 Inch Color CCD Sharp® (or equivalent) no cheap off brands used  
 Horizontal Resolution: 400TV Lines  
 Effective pixel: 510 x 492  
 Illumination: 0 Lux (built-in 18 high output IR LEDs for night vision)  
 Shockproof: 10G  
 Operating temperature: -40°~70°C  
 Power supply: DC 12V (powered by monitor)



Now with our new ADD25F  
 Heavy Duty Mount



574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

A division of Component Solution Services, LLC.

