



SM05C Rear Vision System

5-inch HD Digital LCD screen with ultra-clear image in a durable housing
 3 AV inputs with built in controller for trigger screen activation
 Clear sound speaker, easy to use advance operation menu
 Back-lighted buttons and monitor have auto dimming feature
 Built for demands of commercial use

MONITOR SPECIFICATIONS VTY MK05C

Screen size: 5-inch digital screen (16:9)
 Long life high resolution: 800 x 480 Pixel (RGB)
 System: PAL/NTSC auto per input
 Contrast: 500:1 Brightness: 500 cd/m²
 Power supply: DC 12V~32V with reverse polarity protection
 Operation temperatures: -20°~70°C
 Storage temperature: -30°~80°C
 3 labeled AV inputs with labeled trigger wires, auto blue screen if no signal
 Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality USA Techwell® processor
 Easy to use OSD menu function via buttons & remote: reversing image delay time 0~30s, (for side cameras) Mirror/Normal image, plus horizontal flip per signal channel (text stays in normal view for readability), multi-language, guidelines.



CAMERA SPECIFICATIONS VTY C001C

Image type: 1/3-inch Sharp® color CCD (or equivalent) - no cheap off brands used
 With audio
 Viewing angle: 130°
 Waterproof: IP69K
 System: NTSC
 Aluminum housing waterproof camera with Allen screws for insured positioning
 Horizontal resolution: 400 TV lines
 Effective pixels: 510 x 492
 Minimum illumination: 0 Lux (built-in 18 high output IR LEDs for night vision)
 Shockproof: 10G
 Operating temperature: -40°~70°C
 Power supply: DC 12V (powered by monitor)



Now with our new
 ADD25F Mount



574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

A division of Comonent Solution Services, LLC. Est. 2002

