



SM05F Waterproof Monitor System

Designed specifically to be used outside on Fire Truck Pump panels, this product is ideal for marine and heavy equipment applications. Our most durable monitor with the highest waterproof rating (IP69) on the market. Also, available in 7" systems part # VTY SM07F.

MONITOR SPECIFICATIONS MK05F

Screen size: 5-inch digital screen (4:3)
2 camera inputs using 4-pin aviation plugs
Monitor is waterproof with IP69 rating
Long life high resolution: 640 x480 Pixel (RGB)
Contrast: 500:1
Brightness: 400 cd/m²
Power: DC 12V~32V reverse polarity protection
Operation temperatures: -10°~65°C
Storage temperature: -30°~80°C
Easy to use OSD menu function, Mirror/Normal image, multi-language, trigger wire activation
No sound due to the high waterproof IP69 rating



CAMERA SPECIFICATIONS C0075F

Sensor: 1/4 Sharp® color CCD
(no cheap off brands used)
System: NTSC
Effective pixels: 510 X 492
Horizontal resolution: 420 TV lines
Waterproof rating: IP69K
View angle: 120°
Operation temperature: -20°~70°C
Power supply: DC 12V (powered by monitor)
Minimum illumination: 0 Lux (built-in 12 IR LEDs for night vision)
Automatic heating when the camera's running temperature is below 10°C



574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

Woman-Owned

A division of Component Solution Services, LLC.

Est. 2002

Subject to change without notice