



SMQ7J

Quad Rear Vision System

No blind Spot as with 360 view systems.

7-inch Quad Digital Screen with ultra-clear image. View 4 cameras at once or any combination. For example, all four sides and the system will trigger to one screen when turn signal or reverse is activated.

MONITOR SPECIFICATIONS MKQ7J

Screen size: 7-inch digital screen (16:9)

Built in Quad Multiplexer

Long Life Resolution: 800 x 480 Pixel (RGB)

System: PAL/NTSC selectable

Contrast: 500:1

Brightness: 450 cd/m2

Power supply: DC 12V~24V with reverse polarity protection

Operation temperatures: -30°~70°C

Storage temperature: -40°~80°C

4 AV color coded inputs with color coded trigger wires, auto blue screen if no signal on activated channel

Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: image delay on time 0~10s, (for side cameras) Mirror/Normal image, multi-language featuring adjustable guidelines.



CAMERA SPECIFICATIONS C001J

Horizontal Resolution: 700 TV Lines

TV System: NTSC

Image Type: 1/3 Inch Color CCD Sharp® or equivalent (no cheap off brands used)

Effective pixel: 510 x 492

Illumination: 0 Lux (built-in 20 high output IR LEDs for night vision)

Aluminum housing.

Waterproof: IP69K

Power supply: DC 12V (from monitor)

Shockproof: 10G

Operating temperature: -40°~70°C

Built-in microphone

Viewing angle: 120°

Horizontal Resolution: 700 TV Lines

TV System: NTSC

Image Type: 1/3 Inch Color CCD Sharp® or equivalent



Optional ADD100Z Aluminum Camera Cover Available for J-series Camera

574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

Woman-Owned

A division of Component Solution Services, LLC.

Est. 2002

Subject to change without notice